

# IPXT33D-MWIV1

## 3MP HD-TVI INDOOR MOTORIZED VARIFOCAL IR DOME



### Lens Option

2.8-12mm Motorized Varifocal

### Features

- HD3MP Video Output
- Adopt HDTV Technology
- True Day/Night
- 2.8 – 12mm vari-focal lens
- Motorized Vari-Focal Lens
- OSD menu, 3D DNR, Smart IR
- Up to 90ft IR distance
- True WDR

Must be used with 3MP HD-TVI DVRs

### Specification

Image Sensor	3MP CMOS
Signal System	PAL / NTSC
Effective Pixels	2052(H)*1536(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/25 s to 1/50,000 s
Lens	2.8-12mm @ F1.2 Motorized, Angle of view: 92° – 32°
Day & Night	ICR
Wide dynamic range	120dB True WDR
Synchronization	Internal synchronization
Video Frame Rate	2052*1536@18fps
HD Video Output	1 Analog HD output
CVBS Output	N/A
S / N Ratio	More than 62dB
AGC	Support
D/N Mode	Color/BW/Smart
White Balance	ATW, MWB
BLC	Support
WDR	True WDR 120dB
Working Temperature	-40 °C – 60 °C (-40 °F – 140 °F)
Humidity	90% or less (non-condensing)
Power Supply	12 VDC, 24VAC
Power Consumption	Max. 6W
Weather Proof Ratings	IP66
IR Range	Up to 90 ft
Communication	Up the coax(need UTC controller)
Protocol	Pelco-C(Coaxitron)
Dimensions	Φ5.35" x 4.02"
Weight	1.32 lbs