



EX/HD-SDI Miniature

7 in 1 Mini Square Camera

SDI735-P Series

**EX-SDI 1,2/HD-SDI/AHD/TVI/CVI/CVBS 7-in-1
Mini Square Camera with Pinhole Lens**

- 35 x 35mm Mini Square
- 2MP Sony Exmor CMOS Sensor
- 3MP Mega Lens (Lens options are available)
- 7-in-1 Video Output (Pre-program upon request)
- Ultra Low Light Color Camera
- Color : 0.05Lux
- Sens-up : Color 0.005Lux, B/W : 0.0005Lux
- D-WDR, 3D DNR
- DC12V
- Made In Korea
- NDAA Compliant

Order Information

SDI735-P1	3.7mm
SDI735-F2	3.7mm



*We can customize with other lens options upon request



Infinite Pixels Electronic USA Inc.
11500 S. Eastern Ave. Suite 150 Henderson NV 89052

www.ipxusa.com sales@ipxusa.com



EX/HD-SDI Miniature

7 in 1 Mini Square Camera

SDI735-P Series

EX-SDI 1,2/HD-SDI/AHD/TVI/CVI/CVBS 7-in-1 Mini Square Camera with Pinhole Lens

- 35 x 35mm Mini Square
- 2MP Sony Exmor CMOS Sensor
- 7-in-1 Video Output
(Pre-program up on request)
- 3MP Mega Lens (Lens options are available)
- Ultra Low Light Color Camera
- Color : 0.05Lux
- Sens-up : Color 0.005Lux, B/W : 0.0005Lux
- D-WDR, 3D DNR
- UTC Function
- DC12V

Optional OSD Operation



*Pre-program up on request

- Push the Joystick to RIGHT for 5sec : AHD
- Push the Joystick to LEFT for 5sec : CVBS
- Push the Joystick to UP for 5sec : CVI
- Push the Joystick to DOWN for 5sec : TVI

General Feature Diagram (mm)



Technical Specification

Specification		NTSC / PAL
Image Device		1/2.9 inch 2 MP Sony Exmor CMOS
Total Pixels / Active Pixels		2001(H) x 1121(V) / 1936(H) x 1097(V)
Scanning System		Progressive
Resolution		EX-SDI/HD-SDI 1080P @30fps, 720p/60fps
S/N Ratio		More than 52dB (AGC Off)
Video Output		EX-SDI (MMCX Connector)(HD-SDI option)
		Selectable Output Signal by Optional OSD Key
Minimum Illumination (F1.2, 30IRE)		EX-SDI (MMCX Connector)(HD-SDI option), HD1,TVI,CVI,CVBS(Basic : CVBS)
		COLOR: 0.05Lux COLOR SENS-UP: 0.005Lux / BW SENS-UP: 0.0005Lux
OSD Functions	White Balance	ATW / AWC-SET / INDOOR / OUTDOOR / MANUAL / AWB
	Exposure	MANUAL
	Shutter Speed	AUTO/FLK, 1/30(25) - 1/50000 sec
	Sens-up	AUTO(x4) / x2, x4, x6, x8, x10, x15, x20, x25, x30
	Backlight Compensation	BLC / HSBLC
	Privacy Masking	4 Zone
	Day & Night	AUTO / COLOR / BW / EXT
	Motion Detection	OFF / ON
	2DNR	OFF / LOW / MIDDLE / HIGH
	3DNR	OFF / LOW / MIDDLE / HIGH
	Digital Effect	OFF / MIRROR / V-FLIP / ROTATE & FREEZE
	Sharpness / Defog	Adjustable / ON, OFF
	Image Enhancement	D-WDR
	Language	ENG/CHN1/CHN2/GER/FRA/ITA/SPA/POL/RUS/POR/NED/TUR
Power Input / Consumption		DC 12V (±30%), 100mA
Operation / Storage Temp.		14°F ~ 122°F / -4°F ~ 140°F (-10°C ~ 50°C / -20°C ~ 60°C)
Dimension(mm)		35 x 35 (mm)
Cable		Standard 500mm BNC/DC Jack



Infinite Pixels Electronic USA Inc.
11500 S. Eastern Ave. Suite 150 Henderson NV 89052